

GP® Rechargeable Batteries



Cell Size	Model No.	Nominal Voltage (V)	Capacity (0.2C discharge)*(mAh)		Nominal Dimension (mm)		Weight (g)	Standard Charge		1 Hr Charge
			Minimum	Typical	Diameter	Height		Current (mA)	Time (Hour)	Current (mA)#

High Capacity Series

AAA	85AAAHC	1.2	830	850	10.5	44.5	15	85	16	850
	80AAAHC	1.2	780	800	10.5	44.5	14	80	16	800
	5AAAHC**	1.2	730	750	10.5	44.5	13	75	16	750
AA	220AAHC	1.2	2200	2150	14.5	50.5	29	210	16	2100
	210AAHC	1.2	2000	2050	14.5	50.5	28	200	16	2000
	200AAHC	1.2	1900	1920	14.5	50.5	27	190	16	1900
	180AAHC**	1.2	1750	1800	14.5	50.5	26	180	16	1800
C	400CHC	1.2	3880	4000	26.2	50	8.2	400	16	NA
	350CHC	1.2	3480	3500	26.2	50	78.5	350	16	NA
D	900DHC	1.2	8750	9000	34.2	61.5	173	900	16	NA
	700DHC	1.2	6800	7000	34.2	61.5	170	700	16	NA
	450DHC	1.2	4400	4500	34.2	61.5	130	450	16	NA

Standard Series

AAA	70AAAHC**	1.2	680	700	10.5	44.5	12.2	70	16	700
	65AAAHC	1.2	630	650	10.5	44.5	13	65	16	650
	60AAAHC**	1.2	600	630	10.5	44.5	13	60	16	600
AA	160AAHC**	1.2	1550	1600	14.5	50.5	26	160	16	1600
	130AAHC	1.2	1250	1300	14.5	50.5	26	130	16	1300
C	220CH	1.2	2150	2200	26.2	50	61	220	16	NA
D	220DH	1.2	2150	2200	34.2	61.5	71	220	16	NA

9V Series

9V	17R8H**	8.4	170	175	15.7(T) x 26.5(W) x 48.5(H)32		17	16	170
	17R7H**	7.2	170	175	15.7(T) x 26.5(W) x 48.5(H)28		17	16	170

Prismatic Series

Prismatic	14M145**	1.2	1350	1450	6.1(T) x 17.0(W) x 67.0(H)25		135	16	1350
	14M**	1.2	1250	1400	6.1(T) x 17.0(W) x 67.0(H)23		125	16	1250

One hour rate with charge termination control. * After charging at 0.1 C for 16 hours. ** With UL approval.